



CLEAR SEALER PRODUCT GUIDE

Clear Sealer is a clear semi-gloss water-based acrylic finish designed to protect and beautify tile, concrete, masonry and SoilGlu™ foundation treated surfaces.

WHAT IS CLEAR SEALER USED FOR?

Clear Sealer can be used with:

- SoilGlu[™] foundation treatments
- Concrete and cement
- Masonry and tiles

INTERESTING BENEFITS

- Clear semi-gloss sealer
- Water based
- Easy to apply and clean up
- Easily applied to a wet surface
- Waterproofs porous materials
- Withstands extreme weather
- Resists dirt, grease, and oils
- Helps prevent growth of mould and mildew
- Non-yellowing and UV resistant
- Environmentally friendly

APPLICATION METHODS

Clear Sealer is applied using a surface application method.

WHEN TO USE

Use Clear Sealer to enhance and protect porous surfaces. Apply Clear Sealer at 1L per 5 -7 m^2 area.

APPLICATION METHOD

- 1. Measure application area (m²)
- 2. Calculate Clear Sealer (L) required: 1L Clear Sealer per $5\,\text{-}\,7m^2$
- 3. Purchase required product from Prozyme or an authorised distributor
- 4. Prepare application equipment
- 5. Apply Clear Sealer at an application rate of 1L Clear Sealer per 5 $7m^2$



APPLICATION METHODS CONTINUED

- 6. Adjust application rates where necessary
- 7. Allow to cure for 2 4 hours
- 8. Reapply another coat
- 9. Clean equipment and work area
- 10. Product fully cures after 7 days

CLEAN UP & STORAGE

CLEANING UP

Clean all equipment and tools immediately after use using a soft bristle brush and water.

STORAGE

Store out of direct sunlight and at room temperature.

TECHNICAL INFORMATION

The table below outlines the key technical information.

PPE	Glasses, gloves
COVERAGE	1L per 6m ²
EQUIPMENT	Brush, Roller
CLEAN UP	Scrub, water
COATS	2-3
RECOAT	2-4hrs
DRY	12-24hrs
FULLY CURED	7 days

CONTACT PROZYME

- info@prozyme.com.au
- www.prozyme.com.au
- 28-32 Railway Parade, Welshpool, WA 6106
- 🖻 ACN 666 973 440 | ABN 40 666 973 440